

UNITED FD SAE 60 HEAVY DUTY FINAL DRIVE FLUID



United FD SAE 60 is formulated for use in heavy-duty off-highway truck and bulldozer axles, final drives, differentials, and bevel gears to provide optimum wear protection and component life when used as recommended. United FD SAE 60 is designed to address the extreme pressure (EP) or heavy load-carrying capability needed for final drive gear sets and bearings operating under extreme temperatures and high loads where CAT FD-1 performance fluid is specified. United FD SAE 60 is not recommended for use in compartments that contain friction materials.

Features:

- Optimum wear protection
- Outstanding anti-foam characteristics
- Excellent oxidation and thermal stability
- Compatible with TO-4 oils*

**United FD SAE 60 is recommended for Caterpillar final drives and axles that currently specify the use of CAT TO-4 oil and do not contain friction material.*

TYPICAL SPECIFICATION DATA

UNITED FD 60	
SAE GRADE	60
Viscosity @ 100°C (cSt)	24.0
Viscosity @ 40°C (cSt)	300.5
Viscosity Index	100
Density (lb/gal)	7.47
Pour Point (°C)	-9
Pour Point (°F)	16
Flash Point (°C)	250
Flash Point (°F)	482
Copper Corrosion	1A

Meets or Exceeds:

- CAT FD-1
- CAT FDAO

Contact your local United Account Manager for product availability.