

UNITED SUPER PREMIUM FLEET SYNTHETIC BLEND SAE 10W-30



United Super Premium Fleet Synthetic Blend SAE 10W-30 is an API CK-4 premium heavy-duty diesel engine oil formulated to provide improved wear protection and excellent control of high-temperature oxidation and soot in both new- and older-model engines for on- and off-highway applications. This heavy-duty diesel engine oil also provides better deposit control, reduced oil consumption, improved low-temperature pumpability, and control of soot-related viscosity changes.

Features:

- Measurable improvement in fuel economy versus conventional SAE 15W-40 engine oil.
- Blended with synthetic base oil to improve cold starts and reduce fuel consumption without compromising durability or engine protection.
- Exceptional shear stability and stay-in-grade viscosity beyond the API CK-4 performance category in support of extended drain intervals.*
- High total base number (TBN) technology through a balanced formulation of detergents, dispersants, and other additives to ensure maximum engine protection.
- Unique soot-dispersing technology to diffuse soot to reduce oil thickening.
- Excellent anti-wear, oxidation stability, and corrosion protection for cleanliness and long engine life.
- Enhanced aeration control protects against air, foam, and bubbles to help maintain the integrity of the oil for proper film protection.
- Excellent oil consumption control lowers oil costs due to reduced make-up oil during operation.
- Provides high film strength, excellent low-temperature properties, and viscosity retention during use.

Check owner's manual for the proper SAE grade, API classification, and oil change intervals.

**Always utilize used oil analysis if looking to extend drain intervals.*

TYPICAL SPECIFICATION DATA

UNITED SUPER PREMIUM FLEET SYNTHETIC BLEND SAE 10W-30	
SAE GRADE	10W-30
Viscosity @ 100°C (cSt)	11.7
Viscosity @ 40°C (cSt)	78.0
Viscosity Index	143
Density (lb/gal)	7.22
CCS Viscosity (cP)	5,800
Pour Point (°C)	-36
Pour Point (°F)	-33
Flash Point (°C)	230
Flash Point (°F)	446
TBN	10.5
Sulfated Ash, wt%	1.0

Meets or Exceeds:

- ACEA E9, E7
- API CK-4, CJ-4, CI-4 PLUS, CI-4, CH-4
- Caterpillar ECF-3, ECF-2, DEO-ULS, DEO
- Cummins CES 20086, CES 20081
- Daimler MB 228.31
- Detroit Diesel DFS 93K222, DFS 93K218
- Ford WSS M2C171-F1
- Mack EOS-4.5, EO-O Premium Plus, EO-N
- MAN M3575
- MTU Category 2.1
- Renault RLD-4, RLD-3
- Volvo VDS-4.5, VDS-4, VDS-3

Product Availability:

- 12 x 1 Qt
- 2 x 2.5 Gal
- 30 Gal
- 55 Gal
- 265 Gal
- Bulk
- Item # 236726
- Item # 236725
- Item # 244095
- Item # 236724
- Item # 255711
- Item # 236723