

UNITED SYNTHETIC 2-CYCLE OIL



United Synthetic 2-Cycle Oil is a premium injector and 50/1 premix oil blended with high-quality synthetic base oils and ashless additives for use in a wide variety of two-cycle applications. The carefully balanced additive package included is fit for use in direct fuel-injected, electronic fuel-injected, and carbureted water-cooled and air-cooled engines. This can include outboard engines, snowmobiles, motorcycles, ATVs, personal watercraft, and handheld equipment.

Features:

- Excellent lubricity
- Provides defense from piston damage
- Specially formulated additive package
- Provides clean engine operation and reduced deposits
- Provides superior protection against rust and corrosion
- Enhances engine cleanliness, reliability, and durability
- Synthetic base oils providing improved cold-temperature performance
- Blue color for easy identification

TYPICAL SPECIFICATION DATA

UNITED SYNTHETIC 2-CYCLE OIL	
Viscosity @ 100°C (cSt)	7.3
Viscosity @ 40°C (cSt)	37.8
Viscosity Index	162
Density (lb/gal)	7.22
Pour Point (°C)	-51
Pour Point (°F)	-60
Flash Point (°C)	102
Flash Point (°F)	216
Four Ball Wear Test (mm)	0.715
Brookfield Viscosity (cP), -40°C	14,250
Metals (wt%)	0.0

Recommended Use:

United Synthetic 2-Cycle Oil is a non-licensed product* formulated for two-stroke engines requiring a listed specification for TC-W3, API TC, and JASO FB.

*The additive system has been fully tested and qualified in accordance with the identified specifications in a different combination of base oils than used in these products.

Product Availability:

- 5 Gal
- 55 Gal
- 275 Gal

Contact your local United Account Manager for product availability.